



FOR THE SCOPE OF  
ACCREDITATION UNDER NVLAP LAB  
CODE 100402-0.

# REPORT

3933 US ROUTE 11 CORTLAND, NEW YORK 13045

Project No. G100641836

Date: March 9, 2012

REPORT NO. 100641836CRT-008

TEST OF ONE WALL MOUNT FIXTURE

FIXTURE MODEL NO. RES10-WH

RENDERED TO

MILLENNIUM LIGHTING  
922 DAILEY MILL ROAD  
MCDONOUGH, GA 30253

TEST: Electrical and Photometric tests as required to the IESNA test standard.

LABORATORY NOTE: The laboratory that conducted the testing detailed in this report has been Qualified, Verified, and Recognized for LM-79 Testing for ENERGY STAR for SSL by US DOE's CALiPER program.

STATEMENT OF LIMITATION: This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

AUTHORIZATION: The testing performed was authorized by signed quote number 500357309.

STANDARDS USED: The following American National Standards or Illuminating Engineering Society of North America Test Guides were used in part or totally to test each specimen:

IESNA LM-54: 1999 Guide to Lamp Seasoning

IESNA LM-46-04: 1998 Approved Method for Photometric Testing of Indoor Luminaires Using High Intensity Discharge or Incandescent Filament Lamps

DESCRIPTION OF SAMPLE: The client submitted one sample of model number RES10-WH. The sample was received by Intertek on February 14, 2012, in undamaged condition, and one sample was tested as received. The sample designation was M242869-1.

DATES OF TESTS: March 7, 2012.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program. Measurement uncertainty budgets have been determined for applicable test methods and are available upon request.

SUMMARY

Model No.: RES10-WH
Description: Wall Mount Fixture with a 200 W Incandescent Bulb

Criteria	Result
Total Lumen Output	973.7 Lumens
Total Power	166.5 W
Luminaire Efficacy	5.848
Power Factor	1.000

EQUIPMENT LIST

Equipment Used	Model Number	Control Number	Last Calibration Date	Calibration Due Date
Elgar AC Power Supply	CW1251	--	--	--
Xitron Power Analyzer	2503H	E235	04/20/11	04/20/12
Cole Parmer Hygro Thermometer	445703	T1359	10/26/11	10/26/12
Kikusui DC Power Supply	35-10L	E160	---	---
Sorenson DC Power Supply	DLM150-20E	--	---	---
LSI High Speed Mirror Goniometer	6440	--	02/17/12	03/17/12

TEST METHODS

Seasoning in Each Burn Orientation

The photometric tests were performed after the lamps were seasoned. Before the photometric tests, each bulb was operated in its designated orientation in the appropriate fixture for a time period of 1.5% of its rated hours in accordance with IESNA LM-54 Guide to Lamp Seasoning.

Photometric and Electrical measurements – Distribution Method

A LSI Type C High Speed Model 6440 Mirror Goniometer was used to measure the intensity (candelas) at each angle of distribution for each sample.

Ambient temperature was measured equal to the height of the sample mounted on the Goniometer equipment. Each sample was operated at input rated voltage in its designated orientation. Each sample was allowed to stabilize for at least thirty minutes before measurements were made. Electrical measurements including voltage, current, and power were measured using the Xitron or Yokogawa Power Analyzer.

Some graphics were created with Photometrics Plus software.

Estimated Total Operating Time

Model No.	Total Hours
RES10-WH	1


## RESULTS OF TESTS

### Photometric and Electrical Measurements – Distribution Method

Intertek Sample No.	Base Orientation	Input Voltage (Vac)	Input Current (mA)	Input Power (Watts)	Input Power Factor	Absolute Luminous Flux (Lumens)	Lumen Efficacy (Lumens Per Watt)
RES10-WH							
M242869-1	UP	120.0	1384	166.5	1.000	973.7	5.848

### Intensity (Candlepower) Summary at 25°C - Candelas


Angle	0	22.5	45	67.5	90
RES10-WH					
0	355	355	355	355	355
5	332	334	338	343	352
10	311	313	320	330	347
15	249	263	295	315	337
20	156	170	224	298	329
25	101	110	148	245	320
30	71	78	103	175	307
35	49	54	75	124	266
40	37	40	53	90	200
45	26	30	40	68	141
50	15	19	30	49	99
55	3	7	20	39	75
60	0	0	9	30	56
65	0	0	0	20	43
70	0	0	0	9	34
75	0	0	0	0	24
80	0	0	0	0	14
85	0	0	0	0	4
90	0	0	0	0	0



## RESULTS OF TESTS (cont'd)

### Illumination Plots

Model No.: RES10-WH  
Mounting Height: 10 ft.



### Zonal Lumen Summary and Percentages at 25°C

Zone	Lumens	% Luminaire
RES10-WH		
0-30	260.1	26.7
0-40	414.1	42.5
0-60	714.9	73.4
60-90	232.3	23.9
0-90	947.2	97.3
90-180	26.5	2.7
0-180	973.7	100.0

Picture (not to scale)



CONCLUSION

The results tabulated in this report are representative of the actual test samples submitted for this report only. The data is provided to the client for further evaluation. Compliance to the referenced specification requirements was not determined in this report.

In Charge Of Tests:

A handwritten signature in black ink, appearing to read 'Kenda Branch'.

Kenda Branch  
Engineer  
Lighting Division

Attachment: None

Report Reviewed By:

A handwritten signature in black ink, appearing to read 'David Ellis'.

David Ellis  
Senior Project Engineer  
Lighting Division